

#### SEGAL OPTIKS PRIVATE LIMITED

First Authorized C&F Stockist for Occiore Technologies



+91 98200 27745



chetan@segal.co.in; csegal25@yahoo.com

Poornima Co-op Hsg. Society, Shop No C-005, Near Jaslok Hospital, 23, Peddar Rd, Mumbai - 400026





in collaboration with

SEGAL OPTIKS PRIVATE LIMITED





### OCCIORE **SLIT LAMPS**













+91 87082 22159; Office: +91171 4001119

Q www.occioretech.com

occioretechnologies@gmail.com

1267, 1st Floor Bengali Mohalla, Ambala - 133001, Haryana, India









### Partner with Us at Optika Mumbai 2025

Join Occiore Technologies and expand your portfolio in Ophthalmic Equipment

Visit Our Booth for **Exclusive Opportunities**!

**OPTIKA MUMBAI 2025** 

TRADE FAIR AND EXHIBITION ON OPTICS

February 1,2 & 3, 2025 Nesco, Goregaon East, Mumbai



Booth # E 28A

 $\mathcal{Q}$ 

www.occioretech.com



www.segal.co.in



# **SLIT LAMP MICROSCOPE**

	Model Variants	2 step	3 step	5 step
OPTICAL SYSTEM	Туре	Galilean	Galilean	Galilean
	Magnification	1x, 1.6x	5x, 10x, 20x	6x, 10x, 16x, 25x, 40x
	Eyepiece	10x, 15x	12.5x	12.5x
	Objective Lens Focal Distance	95mm	100mm	100mm
	Aperture	0.2, 1, 3, 5, 8 & 12mm		
SLIT PROJECTION	Filters	Cobalt Blue, Red Free, Heat Absorbing Milky White and Warm White		
	Slit Rotation	+ / - 90 Degree		
	Slit Vertical Tilt	0, 5, 10, 15 Degree		
	Base Tilt	X-axis 100mm; Y-axis 110mm; Z-axis 25mm		
SYSTEM AND BASE	Horizontal Fine Adjustment	12mm		
	Table Top Dimension	320mm x 330mm		
	Fixation Lamp Light Source	LED		
	LED Source	LED / HALOGEN		
	LED Output	100K		
POWER SUPPLY	Power Supply Unit	120 to 280 Volt Input 1 Ampere (SMPS) 9V / 3 WLED (SMPS)		
	Fuse	1 Ampere		
PO	Power Supply Output	12V 50W Halogen		
	Slit Lamp Complete - Dimensions Packed	290mm x 440mm x 700mm (Approx)		
	Slit Lamp Complete - Weight Packed		15 Kg (Approx)	



## **ZEISS STYLE SLIT LAMP**

#### **KEY FEATURES:**

- Integrated fixation target for patient alignment
- Optional mount for Applanation Tonometer

OPTICAL SYSTEM	Туре	Galilean optical system	
	Magnification Levels	2-step: 10x, 16x 3-step: 10x, 16x, 25x 5-step: 6x, 10x, 16x, 25x, 40x	
	Eyepiece	10x and 5x wide-field	
	Field of View	10x (18mm), 16x (14.5mm), 25x (8.8mm) 40x (5.5mm)	
	Diopter Adjustment	-5D to +5D	
SLIT ILLUMINATION	Light Source	LED	
	Slit Width	0 - 12mm (continuously adjustable)	
	Slit Length	0.2mm to 12mm	
	Slit Apertures	0.2mm, 1mm, 3mm, 5mm, 8mm, 12mr	
	Filters	Cobalt Blue, Light Diffuser, Red-free (Green), Neutral Density, Light Blue, Yellow, Light Green	
	LED Output	100K	
MECHANICAL ADJUSTMENT	Joystick Control	Smooth joystick with fine focus adjustment	
	Chin Rest Adjustment	70mm vertical range	
	Power Supply - Input	110V-240V AC, 50/60 Hz	